



# M90-D1-C

## Chemical Warfare Agent Detector



M90. The right choice for the 21st Century. Today's Chemical Warfare threat surpasses the traditional battlefield environment, and places the public and local First Responders in harm's way to an extent that has never been experienced before. This expanded role requires more than a traditional Chemical Detector; it necessitates a system that is proven, reliable and affordable, but first and foremost one that performs when called upon.

- Fielded in both land and naval environments from the great deserts to the frozen Arctic M90 has proven its ruggedness and operational readiness.
- In urban, fixed installations such as in Subway systems M90 has proven its long-term reliability while operating 24 hours a day, 7 days a week for minimal maintenance costs.
- Across the board, M90 has demonstrated greater readiness and lower Life-Cycle Support costs than its competitors; and meets or exceeds current US requirements for detection performance while delivering outstanding interference rejection.

### Features And Benefits

- Fast detection of all current threat CWAs
- Continuous real time operation
- Multi-role, Detector and Monitor
- Broad range of operating and storage environments
- Maintenance free storage
- Low Life-cycle Support Costs
- Proven performance in both open air and laboratory agent/interferent environments
- Flexible communications interface and network ready

# M90-D1-C

## Chemical Warfare Agent Detector

### Technical Data

**Size (H x W x L):**

280 x 105 x 280 mm (11 x 4.1 x 11 in.)

**Weight:**

4.7 kg (10.4 lbs) w/o battery

**Power:**

12 Vdc, 85...264 Vac with Power Supply

**Battery:**

NiMH (rechargeable) or Lithium Sulfur Dioxide (NSN)

**Data Interface:**

RS-232 or RS-485

### NATO Stock Number

6665-01-408-5108

### Agent Sensitivity

Nerve < 0.1 mg/m<sup>3</sup>

Blister < 2.0 mg/m<sup>3</sup>

### Environmental

**Operating Temperature:**

-30 to +55°C (-22 to +131°F)

**Storage Temperature:**

-40 to +55°C (-40 to +131°F)

**Shock:**

MIL-STD-810D

**Vibration:**

MIL-STD-810D


**EMI:**

MIL-STD-461C

**EMP:**

MIL-STD-462

*T i m e   d o e s   m a t t e r .   W e   a r e   r e a d y   f o r   t h a t .*



**Environics**

**Environics Oy**  
P.O. Box 349  
FI-50101 Mikkeli  
Finland  
Tel: +358 201 430 430  
Fax: +358 201 430 440  
E-mail: sales@environics.fi  
www.environics.fi

**Environics USA, Inc.**  
4401 Eastport Parkway  
Port Orange, FL 32127  
USA  
Tel: +1 386 304 5252  
Fax: +1 386 304 5251  
E-mail: sales@environicsusa.com  
www.environicsusa.com